

2024 Fall Specials

Quarterly Special valid from October 1st – December 31st, 2024

Ethernet media converters

Reliable communication via fiber optics

NEW

For high-level immunity to interference and long transmission ranges in industrial applications, media converters transparently convert Ethernet data to fiber optics. Depending on the device and cable, they bridge distances of up to 80 km at data rates of up to 1 Gbps. 36 variations to suit every application. Designed to work with both store and forward or passthrough application.



Your advantages

- ✓ MC1000, Standard series for general industrial use
- ✓ MC 1000T, adds onto the standard series with extended temperature range, redundant power supply inputs, digital alarm, and extended approvals; cUL EX Listed and DNV/GL
- ✓ MC 1000E, expands on the 'T' variation adding ATEX and IEC 61850/IEEE1613 — Coming Q4 2024

| Order no. | Description | Promo Price |
|-----------|----------------|-------------|
| 1329817 | MC 1000-MM SC | \$190 |
| 1329818 | MC 1000-MM ST | \$190 |
| 1329827 | MC 1000T-MM SC | \$280 |
| 1330244 | MC 1000T-MM ST | \$280 |

[View full product range](#)

All orders must reference promo code *****FALL2024*****. Quarterly Special valid from October 1st – December 31st, 2024. All prices are customer net each.

*Please note that ALL pricing is in CAD and this special is only available in Canada

ECM-UC Series Current Transducers

NEW

We are thrilled to introduce the latest innovation in our current transducer family, set to replace the older MCR-S series, previously in a green housing.

The new ECM series offers more versatility, accuracy, and ease of configuration with a user-friendly interface, in a redesigned grey housing. Easily configurable by DIP switches or using a USB connection via a web based management system.




| Order no. | Description | Input Range | Output Type | Promo Price |
|-----------|--------------------|---------------------------|----------------|-------------|
| 1698164 | ECM-UC-10A-UI-REL | 0 A AC/DC ... 10 A AC/DC | Analog + Relay | \$449 |
| 1136504 | ECM-UC-10A-UI | | Analog | \$404 |
| 1698172 | ECM-UC-100A-UI-REL | 0 A AC/DC ... 100 A AC/DC | Analog + Relay | \$449 |
| 1136513 | ECM-UC-100A-UI | | Analog | \$389 |
| 1191969 | ECM-UC-10A-MRTU | 0 A AC/DC ... 10 A AC/DC | Modbus/RTU | \$424 |
| 1191986 | ECM-UC-100A-MRTU | 0 A AC/DC ... 100 A AC/DC | Modbus/RTU | \$449 |
| 1191970 | ECM-UC-10A-MTCP | 0 A AC/DC ... 10 A AC/DC | Modbus/TCP | \$499 |
| 1191984 | ECM-UC-100A-MTCP | 0 A AC/DC ... 100 A AC/DC | Modbus/TCP | \$524 |

Features

- ✓ Configurable using web based page or DIP Switches
- ✓ USB-C Connection provides power for configuration
- ✓ Less than 0.5% error margin
- ✓ Modbus TCP/RTU version available

DIN Rail Adapter, RJ45 Modules, and Accessories



| Details | Kit, adapter with RJ45 IDC jack | RJ45 Modules, Cat6A 1417274 is included with 1100077 | | Plug Guard Security Frame • Prevents accidental disconnects | Port Guard Security Element • Prevents unauth. connections | Stripping Tool for shielded cables |
|-------------|--|--|---------|---|--|------------------------------------|
| Order no. | 1100077 | 1041760 | 1417274 | 1041881 | 1041900 | 1657407 |
| Promo Price | \$24.38 | \$26.17 | \$17.15 | \$5.36 | \$5.36 | \$175.51 |
| Details | Adapter only, order RJ45 Module separately | Designed for demanding Ethernet applications with up to 10Gbit/sec data transmission in accordance with Cat6A. Patch cables feature a protected locking clip and are available in standard lengths up to 20m. One-piece DIN rail adapter snaps easily into place and can be configured for secure connections. Ideal for building automation and control cabinet applications. | | | | |
| Order no. | 1041740 | | | | | |
| Promo Price | \$11.80 | | | | | |

RJ45 Industrial Ethernet Patch Cables, LSZH jacket, grey

| Length | 0.3m | | 0.5m | | 1.0m | | 1.5m | | 2m | | 3m | |
|--------------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|
| | Order no. | Promo Price | Order no. | Promo Price | Order no. | Promo Price | Order no. | Promo Price | Order no. | Promo Price | Order no. | Promo Price |
| CAT5 up to 1Gbps | 1227558 | \$8.54 | 1227559 | \$9.06 | 1227560 | \$9.81 | 1227561 | \$10.60 | 1227562 | \$11.33 | 1227563 | \$12.93 |
| CAT6A up to 10Gbps | 1227572 | \$11.59 | 1227573 | \$12.16 | 1227575 | \$12.99 | 1227578 | \$13.82 | 1227580 | \$14.64 | 1227581 | \$16.93 |


ⓘ Ask us about different jacket colour options for Cat6A cords — now available!



Uninterruptible Power Supplies (UPS) DC Power

For critical applications, Uninterruptible Power Supplies (UPS) can provide a lifeline to keep your system up and running.

| Order no. | Description | Comms | Amps | Promo Price |
|-----------|-----------------------------|---------------|------|-------------|
| 2906990 | QUINT4-UPS/24DC/24DC/5 | — | 5A | \$336 |
| 2907066 | QUINT4-UPS/24DC/24DC/10 | — | 10A | \$370 |
| 2907071 | QUINT4-UPS/24DC/24DC/20 | — | 20A | \$435 |
| 2907077 | QUINT4-UPS/24DC/24DC/40 | — | 40A | \$762 |
| 2906991 | QUINT4-UPS/24DC/24DC/5/USB | USB | 5A | \$385 |
| 2907067 | QUINT4-UPS/24DC/24DC/10/USB | USB | 10A | \$419 |
| 2907072 | QUINT4-UPS/24DC/24DC/20/USB | USB | 20A | \$472 |
| 2907078 | QUINT4-UPS/24DC/24DC/40/USB | USB | 40A | \$803 |
| 2906994 | QUINT4-UPS/24DC/24DC/5/EIP | EIP/ModbusTCP | 5A | \$528 |
| 2907069 | QUINT4-UPS/24DC/24DC/10/EIP | EIP/ModbusTCP | 10A | \$565 |
| 2907074 | QUINT4-UPS/24DC/24DC/20/EIP | EIP/ModbusTCP | 20A | \$634 |
| 2907080 | QUINT4-UPS/24DC/24DC/40/EIP | EIP/ModbusTCP | 40A | \$966 |
| 2906993 | QUINT4-UPS/24DC/24DC/5/PN | PROFINET | 5A | \$528 |
| 2907068 | QUINT4-UPS/24DC/24DC/10/PN | PROFINET | 10A | \$565 |
| 2907073 | QUINT4-UPS/24DC/24DC/20/PN | PROFINET | 20A | \$634 |
| 2907079 | QUINT4-UPS/24DC/24DC/40/PN | PROFINET | 40A | \$966 |
| 2906996 | QUINT4-UPS/24DC/24DC/5/EC | ETHERCAT | 5A | \$536 |
| 2907070 | QUINT4-UPS/24DC/24DC/10/EC | ETHERCAT | 10A | \$572 |
| 2907076 | QUINT4-UPS/24DC/24DC/20/EC | ETHERCAT | 20A | \$634 |
| 2907081 | QUINT4-UPS/24DC/24DC/40/EC | ETHERCAT | 40A | \$966 |



Power supply
AC-to-DC, DC-to-DC power supplies



UPS module
Selected based on output requirements



Energy-storage device
Select the appropriate energy storage for your modular system

Energy storage type — UPS-BAT/PB

| Load current | Buffer time | | | | | | | | | | | | | | | | | | | | Energy storage | | | |
|--------------|-------------|---|---|---|---|---|---|---|----|----|--------|----|----|----|---|---|---|---|---|----|----------------|----|--|--|
| | Minutes | | | | | | | | | | Hours | | | | | | | | | | | | | |
| | 1 | 2 | 3 | 5 | 6 | 7 | 8 | 9 | 10 | 20 | 30 | 40 | 45 | 50 | 1 | 2 | 3 | 5 | 8 | 10 | 15 | 20 | | |
| 1 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Green | | | |
| 2 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 3 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 5 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 7 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 10 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 15 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 20 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 25 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 30 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 35 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 40 A | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 1.2 Ah | Green | | | | | | | | | | Yellow | | | | | | | | | | Green | | | |
| 4 Ah | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 7 Ah | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 12 Ah | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 1274119 | Green | | | | | | | | | | Yellow | | | | | | | | | | Green | | | |
| 1348516 | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |
| 1354641 | Green | | | | | | | | | | Yellow | | | | | | | | | | Yellow | | | |


1+1 ... Two energy-storage types of the same capacity are required, based on ambient temperature of 20°C.

Energy storage type — LI-ION or VLRA-WTR

| Load current | Buffer time | | | | | | | | | | | | | | | | | Energy storage | | | | | | |
|--------------|-------------|----|----|---------|---|---|---|-------|---|---|---|----|----|----|----|----|----|----------------|---|---|---|---|----|----|
| | Seconds | | | Minutes | | | | Hours | | | | | | | | | | | | | | | | |
| | 10 | 15 | 30 | 1 | 2 | 3 | 5 | 6 | 7 | 8 | 9 | 10 | 20 | 30 | 40 | 45 | 50 | 1 | 2 | 3 | 5 | 8 | 10 | 15 |
| 1 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 2 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 3 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 5 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 7 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 10 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 15 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 20 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 25 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 30 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 35 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 40 A | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 1396415 | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 2320416 | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 128 Wh | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| \$957.00 | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 2320429 | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| 26 Ah | Green | | | | | | | | | | | | | | | | | Green | | | | | | |
| \$1,691.00 | Green | | | | | | | | | | | | | | | | | Green | | | | | | |

1+1 ... Two energy-storage types of the same capacity are required, based on ambient temperature of 20°C.

25 years of
 CLIPLINE complete




Order a FREE sample online

Watch the PUSH-X video

Push-X

Welcome to the next era

The tool-free conductor connection. Push-X can accommodate all types of conductors without the need for force or tools.



Your advantages

- ✓ For any application using conductors without ferrules for a much faster wiring even compared to our market leading Push-in Technology
- ✓ Secure connection thanks to its spring technology
- ✓ From 20AWG to 6AWG - up to 55A
- ✓ Tool free operation with flexible conductor without pre-treatment
- ✓ Fully compatible with all Phoenix contact terminal block accessories from the CLIPLINE Complete
- ✓ Best in class to upgrade any screw type terminal block panels with minor changes in the layout of your panel

New Automatic Stripping device

NEW

E. FOX S10

With the electric E.FOX S10 automatic stripping device, you can strip wires with different cross-sections and types of insulation easily and efficiently.

- The compact automatic stripping device can be integrated into and controlled via worker assistance systems
- The touch display makes operation intuitive.
- Settled favorites can be linked to a bar code and accessed using a handheld scanner for faster repeat project
- Stripping length: 2mm ... 20mm
- From 28AWG to 8AWG

